



Strapping Band DIC PP Band

Suitable for bundling goods, preventing load collapse, and supporting transportation.

Features of DIC PP Band

- Suitable for packaging a wide range of products.
- Since it does not absorb water, its strength remains unchanged even when wet.
- Several types are available for automatic strapping machines to meet various needs.
- Some models for automatic strapping machines use Pla-Core to address the issue of paper core disposal.

Product Specifications of DIC PP Band

■ PP Band for DIC Stopper Fastening

Product Name	Width (mm)	Length (m)	Tensile Strength (N/kgf)	Elongation (%)	Inner Diameter (Ø)	Packaging (rolls)
P15.5	15	1000	980/100	20	150	5

[Fastening Tool] [DIC PP Band Stopper](#)

■ PP Band for Metal Seal Fastening

Product Name	Width (mm)	Length (m)	Tensile Strength (N/kgf)	Elongation (%)	Inner Diameter (Ø)	Packaging (rolls)
SS15.5	15	1000	1270/130	25	150	5
SS19	19	1000	1570/160	25	150	5

[Strapping Equipment] [Tensioners, Case Sealers, and Metal Seals](#)

■ PP Band for Automatic Strapping Machines

Product Name	Width (mm)	Length (m)	Tensile Strength (N/kgf)	Elongation (%)	Inner Diameter (Ø)	Packaging (rolls)
HM6	6	4000	780/80	20	200	2
H9	9	3000	880/90	25	200	2
HM12	12	3000	1080/110	25	200	2
HM15.5	15	2500	1370/140	25	200	2
HM19	19	2000	1670/170	25	200	2
Fine12	12	3000	980/100	20	200	2
Fine15	15	2500	1180/120	20	200	2
SUPER Fine12	12	3000	980/100	20	200	2
SUPER Fine15	15	2500	1180/120	20	200	2
HMS12	12	3500	980/100	20	200	2
	12	4500	980/100	20	200	2
HMS11	11	5000	980/100	20	200	2
HMS15.5	15	2500	1180/120	20	200	2
HMX15.5	15	3300	1180/120	20	200	2
HZ14	14	5000	980/100	20	200	1
B15.5	15.5	2000	1370/140	25	250	2

■ Foamed Band

Product Name	Width (mm)	Length (m)	Tensile Strength (N/kgf)	Elongation (%)	Inner Diameter (Ø)	Packaging (rolls)
F9	9	2000	690/70	20	200	2
F12	12	3000	880/90	20	200	2
F15.5	15	2500	1180/120	20	200	2

■ PP Band for Tabletop Strapping Machines

Product Name	Width (mm)	Thickness (mm)	Length (m)	Tensile Strength (N/kgf)	Elongation (%)	Inner Diameter (Ø)	Packaging (rolls)
ST9	9	0.58	500	880/90	25	70	12
ST9 Foamed	9	0.47	500	590/60	20	70	12

