



Strapping Band

DIC Ester Band (Heat-Sealing Type)

polyester strapping band offering excellent heat-sealing strength and compatible with automatic strapping machines.

[Applications]

Pallet packaging / Paperboard packaging / Steel sheet packaging / Cotton material packaging / Bulk packaging / Construction material packaging / Bale packaging / Ingot packaging / Export packaging / Others

Features of DIC Ester Band (Heat-Sealing Type)

- Provides outstanding heat-sealing strength, fully utilizing the material's performance.
- Supports labor-saving and production line automation when used with automatic strapping machines for ester bands.
- Improves work efficiency when used with hand tools.

Product Specifications of DIC Ester Band (Heat-Sealing Type)

■ S Type for Heat-Sealing Fastening

Product Name	Width (mm)	Length (m)	Tensile Strength (N/kgf)	Elongation (%)	Inner Diameter (Ø)	Packaging (rolls)
S125	12	2500	2650/270	15	200	1
S164	15.5	2500	2750/281	15	200	1
S164E	15.5	2500	2550/260	15	200	1
S165	15.5	2000	3430/350	15	200	1
S165E	15.5	1800	3240/331	15	200	1
S166E	15.5	1500	3920/400	15	200	1
S194	18.8	2000	3330/340	15	200	1
S195	18.8	1800	4220/431	15	200	1
S195E	18.8	1500	3920/400	15	200	1
S196	18.8	1500	5000/510	15	200	1
S196E	18.8	1300	4710/481	15	200	1

■ Z Type for Heat-Sealing Fastening

Product Name	Width (mm)	Length (m)	Tensile Strength (N/kgf)	Elongation (%)	Inner Diameter (Ø)	Packaging (rolls)
Z168	16	1400	5390/550	20	400	1
Z198	19	1200	6370/650	20	400	1
Z1910F-S	19	800	8000/816	20	400	1

