



Stretch Film Pallet Stretch Wrapping Machine

Stretch film packaging can be performed quickly, safely, and reliably with a pallet stretch wrapping machine.

Features of Pallet Stretch Wrapping Machine

- By utilizing the speed difference between rollers, the stretch film can be extended up to four times, reducing material running costs. Reduces material running costs through the pre-stretch function.
- A robust structure designed with durability as the top priority.
- Ultra-low-profile design for easy pallet loading.
- The film lifting speed and turntable rotation speed are adjustable.
- A model for large pallets with a table size of Ø1,800 mm (PW-1821A) is also available.

Product Specifications of Pallet Stretch Wrapping Machine

Model		PW-1521Ri
Table Size		Ø1,500mm
Maximum Wrapping Height		2,100mm(Including Pallet)
Maximum Load Weight		Max. 2,000 kg
Turntable Speed		5~15RPM
Carriage Speed		Max. 2-5 m/min
Tension Mechanism		Pre-Stretch Type
Applicable Film	Core Inner Diameter	76mm
	Maximum Outer Diameter	280 mm or less
	Width	500mm
	Film Thickness	Recommended: 17-25 μ or more
Power Supply		3-Phase 200 V, 50/60 Hz, 1.6 kW

- Ramp
- Top Press Plate

※For other specifications, please contact us for consultation.

※Machine dimensions do not include the loaded stretch film.

Fully Automatic Pallet Stretch Wrapping Machine: Fully Automatic Type (PW-1223ARD)



- By utilizing the speed difference between rollers, the stretch film can be extended up to four times, reducing material running costs (pre-stretch function).
- The conveyor is sold separately.
- When wrapping above the product height, the film height varies depending on the carriage speed.
- A fully automatic model that can be integrated into a system line. Custom specifications are available to meet a wide range of needs.